

PUREDRI

SUMMARY

Utilising best-in-class sanitising technology the PureDri station provides a triple action defence against the spread of odours, bacteria and viruses in washrooms.

Designed to deliver three points of infection control, fast-dry hand drying and exceptional energy efficiency, the PureDri will substantially reduce contamination risk whilst creating cleaner, fresher smelling and more sustainable washroom environments.

TECHNICAL SPECIFICATIONS

Dimensions	270mm wide x 820mm high x 100mm deep
Weight	9.2 Kg
Electrical Supply	110/240 volts 50/60 Hz
Current Consumption	1.7 Amps @ 115 Volts / 0.9 Amps @ 230 Volts
Room Sterilising / Dryer Standby Current Consumption	0.19Amps @ 115 Volts / 0.14 Amps @ 230 Volts
Nominal Output	213 - 202 kW
Drying Speed	Fast Dry
Operation	Room Sanitising: Continuous Hand Drying & Sanitising: Automatic, infrared, no touch
Sensor Range	100mm vertically under outlet
Air Volume	34 m ³ /h
Air Velocity	50 m/s @ 100mm
Air Outlet Temperature	30°C @ 20°C ambient
Noise Level	85 dBA
Door Colour	Brushed Stainless Steel
End Cap Colours	White (standard)
Installation	Wall mounted vertical
Lamp Options (ozone generating)	3mg Ozone Bulb 0mg Ozone Bulb

